

SCANCLIMBER® SC1000 Mast climbing work platform

SC1000



Transportation by towable trailer chassis



Technical data	SC1000 single	SC1000 twin
• Max. platform length / loading capacity	4,1 m / 1300 kg 7,1 m / 800 kg 10,1 m / 500 kg	12,3 m / 1700 kg 16,8 m / 1400 kg 19,8 m / 1200 kg 25,0 m / 750 kg
• Max. freestanding height - mast side outriggers fully opened	6 m	6 m
• Max. height with top anchor	11,5 m	11,5 m
• Max. height with mast anchored	100 m	100 m
• Distance between anchors	6 m	6 m
• Max. telescopic extensions	1,0 m	1,0 m
• Max. jack load	15 kN	15 kN
• Transport weight - max. (10,1 m platform) - min. (4,1 m platform)	1800 kg 1000 kg	
• Lifting speed	6,0 m / min.	6,0 m / min.
• Mast section, hot dip galvanized	1,5 m / 48 kg	1,5 m / 48 kg
• Electric system - lifting motor	400 V/50 Hz/3 kW 3 phase/32 A	2x400 V/50 Hz/3 kW 3 phase/32 A
• Safety devices - overspeed safety brake - emergency stop and limit switches - electromagnetic brake - phase sequency relay - residual current device	◆ ◆ ◆ ◆	◆ ◆ ◆ ◆
• Options	Self propelled drive for the wheel chassis	

Technical data